



Thermo Scientific Orion VERSA STAR 30

RDO/Dissolved Oxygen Benchtop Meters

BOD testing is complicated enough – no need for the meter to add to the confusion. The large color display is easy to read and easy on the eyes. Prompts make accuracy and repeatability easy for even the most complicated testing. If you need to add more channels or obtain more parameters from the same, simply remove the protective individual channel cover and add the new module.

Discover the most advanced features in our new Orion VERSA STAR meters.



Features and Benefits

- Versatility is the name of the game
 - Customize the display to show only the information you need
 - Change modules to create the meter you need at any time
- Takes the worry out of DO probe compatibility – the meter accepts and automatically recognizes Orion polarographic and RDO optical/luminescence-based probes
- Compensates automatically for temperature, salinity with manual input and barometric pressure (automatic or manual)
- Allows for calibration using water-saturated air, air-saturated water, a Winkler titration or zero point
- Anyone can use this meter with its plain language screen prompts, function keys that update for easy selection and a multilanguage interface that supports English, Spanish, French, Italian, German and Chinese
- Don't miss a reading – AUTO-READ™ locks in the stable reading on your screen, ready indicator alerts when readings are stable and timed reading gathers data in specific time intervals or just once with single-shot mode
- Non-volatile memory holds up to 2000 data points with time and date stamp
- Stores up to 10 methods per channel allow for customized procedures to differentiate between tests and/or users
- Two USB and a RS232 port makes for easy data transfer and updating meter software
- Complimentary data analysis software for easy transferring of stored results or real-time viewing
- Control sample mixing directly from the meter without a separate stir plate when using with the Orion Star stirrer probe (cat. no. 096019, sold separately)
- Increase your productivity – with two Orion Star stirrer probe ports, add stirrers and modules to analyze two separate samples at the same time
- Included electrode arm and newly-designed probe holder make it easier to maintain and place probes into samples
- Works with almost every AC power source through the included universal power adapter
- IP54-rated housing handles splashes and cleans up easily
- 3 year meter replacement warranty



Product Specifications – Orion VERSA STAR Meter

CE TUV EPA		
Maximum Number of Modules	4	
Methods	Up to 10 per channel	
Datalogging	Number of Datalogs	2000 with time and date stamp
	Log Function	Manual, AUTO-READ™, timed interval, single shot reading
Communication Ports	One RS232, one bidirectional USB, one printer-dedicated USB	
Orion Star Stirrer Probe Ports	2	
Power	Universal, AC power adapter, 90-260 VAC, 50-60 Hz	

Meter Ordering Information

Cat. No.	Description
VSTAR30	Orion VERSA STAR RDO/Dissolved Oxygen Benchtop Meter Set - Orion VERSA STAR meter - Orion VERSA STAR dissolved oxygen/temperature module - Electrode arm with redesigned holder - Universal power adapter
	Orion VERSA STAR RDO/Dissolved Oxygen Benchtop Meter Kit - Orion VERSA STAR meter - Orion VERSA STAR dissolved oxygen/temperature module - 083005MD Orion polarographic DO probe - 080017 calibration sleeve for DO probe - 080513 DO probe maintenance kit - BOD adapter, funnel and stirrer - Electrode arm with redesigned holder - Universal power adapter

Product Specifications – RDO/DO Module (VSTAR-RD)

CE TUV EPA		
Dissolved Oxygen	Concentration - Polarographic	
	Range	0 to 90 mg/L
	Resolution	0.01, 0.1
	Relative Accuracy	±0.2
	% Saturation - Polarographic	
	Range	0 to 600
	Resolution	0.1, 1
	Relative Accuracy	±2 %
	Concentration - RDO	
	Range	0 to 50 mg/L
	Resolution	0.01, 0.1
	Relative Accuracy	±0.1 mg/L up to 8 mg/L; ±0.2 mg/L from 8 to 20 mg/L; 10 % of reading, 20 to 50 mg/L
	% Saturation - RDO	
	Range	0 to 500
	Resolution	0.1, 1
	Relative Accuracy	±2 %
	Automatic Barometric Pressure Correction	450.0 to 850.0 mm Hg
	Salinity Factor Correction	Automatic when used with conductivity module and probe or manual; 0 to 45 ppt
Calibration Features	Water saturated air, air saturated water, manual (Winkler) and zero point	
Probe Type	Polarographic or RDO	
Temperature	Range	0 to 50 °C, 32 to 122 °F
	Resolution	0.1
	Relative Accuracy	±0.1
	Offset Calibration	1 point
Input	9-pin mini-DIN	

Accessories

Cat. No.	Description
VSTAR-PH	Orion VERSA STAR pH/temperature module
VSTAR-ISE	Orion VERSA STAR pH/ISE/temperature module
VSTAR-CND	Orion VERSA STAR conductivity/temperature module
VSTAR-RD	Orion VERSA STAR RDO/DO/temperature module
VSTAR-LR	Orion VERSA STAR pH/temperature with LogR technology module
STARA-BEA	Benchtop electrode arm for Orion Star A-series meters
STARA-HB	Freestanding base for use with Orion Star A-series benchtop electrode arm
STARA-PWR	Replacement universal power adapter for Orion VERSA STAR meters
096019	Orion Star stirrer probe
083005MD	Orion dissolved oxygen probe, polarographic
086030MD	Orion auto-stir DO/BOD probe, polarographic
087010MD	Orion RDO optical DO probe, 3 m cable
080513	Maintenance kit, includes electrolyte solution, polishing disk, and two membrane caps for 083005MD and 086030MD
080514	Polarographic electrolyte solution for 083005MD and 086030MD
086021A	Replacement calibration chamber/stand for 086030MD
087001	Replacement optical/luminescence-based cap

pH ■

ISE ■

ORP ■

Cond ■

RDO ■

DO ■

Temp ■